

PMAX-0320



Tilted Wall Mount for Indoor Hemispheric Cameras with IR LED

► Specifications

Device





Product Type	Camera Mount
Application Environment	Indoor
Description	Tilted Wall Mount for Indoor Hemispheric Cameras with IR LED

General

Weight	84.5g (0.19lb)
Dimensions	(Ø x H): 150mm x 34mm (5.91" x 1.34")
Color	Warm Gray
Material	Plastic
Warranty	1 Year(s). For extended warranty offering, see http://www.acti.com/support/warranty
Tilted Angle	10°

▶ Related Products

Dome - Hemispheric Dome

B511A		12MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics
B57		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:187°), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics
B57A		6MP Video Analytics Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics
Q51		2MP Heat Map Indoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:171°), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, DI/DO, Built-in Analytics